



ANALYSIS OF NATURAL GAS DRYING TECHNOLOGIES AND STRATEGIES FOR ENHANCING THEIR EFFICIENCY

Mutalipova Diloromkhon Bakhtiyorjon qizi – Lecturer,
Department of Chemistry and Oil-Gas Technologies, Bukhara
State University

d.b.mutalipova@buxdu.uz

Rahimboyev Khursand Ikrom ugli – 4th year student of the
Oil and Gas Chemistry and Industrial Technology program at
Bukhara State University

Abstract: *Natural gas is one of the most important energy carriers in the global economy, yet its effective use largely depends on ensuring the removal of moisture from the raw stream. The presence of water vapor in natural gas leads to corrosion of pipelines, formation of hydrates, and a decrease in operational reliability of technological equipment. Therefore, gas dehydration remains one of the most essential processes in gas preparation for transportation and industrial applications. This paper presents a comprehensive analysis of conventional and modern gas drying technologies, including absorption, adsorption, condensation, and membrane-based methods. Each method is evaluated in terms of efficiency, energy consumption, operational reliability, and environmental impact. The study further discusses strategies for enhancing the performance of gas dehydration, with emphasis on energy-efficient solutions, innovative sorbent and membrane materials, and integrated process schemes. The results of this analysis provide practical recommendations for improving the efficiency of natural gas drying technologies, contributing to sustainable and cost-effective industrial development.*

Keywords: *Natural gas, dehydration, absorption, adsorption, condensation, membrane technologies, energy efficiency.*

Natural gas has become one of the most significant energy resources in the global economy, playing a crucial role in power generation, industrial production, and household consumption. The efficiency of its utilization largely depends on the proper removal of moisture from the raw gas stream. The presence of water vapor

in natural gas leads to several operational challenges, including accelerated corrosion of pipelines, hydrate formation that may block transmission lines, and a general decrease in the reliability of technological equipment. In addition, excess moisture reduces the calorific value of natural gas and negatively affects its quality parameters for end users.

Gas dehydration is therefore considered a mandatory stage in modern gas processing plants. However, each dehydration technology comes with its own advantages and limitations. For instance, glycol-based absorption methods are widely applied in industry, but they require significant energy input and incur high operational costs. Adsorption technologies ensure deep dehydration levels, yet they involve complex and energy-intensive regeneration processes. Condensation-based cooling methods are relatively simple and inexpensive but remain less efficient at low pressures. In recent years, membrane technologies have emerged as a promising alternative, although their large-scale industrial application is still under development.

This paper provides a comprehensive analysis of existing gas dehydration technologies, evaluating their operational performance and highlighting the main criteria for efficiency assessment. Furthermore, it explores strategies for improving the overall effectiveness of gas drying processes, focusing on innovative materials, energy-saving solutions, and process integration. The findings of this study aim to contribute practical recommendations for enhancing the sustainability, cost-effectiveness, and reliability of natural gas dehydration technologies.

The problem of natural gas dehydration has been widely studied by researchers, as the removal of water vapor is a critical prerequisite for reliable gas transportation and processing. Early studies emphasized the role of moisture in hydrate formation and corrosion, which became the foundation for the development of the first industrial dehydration technologies. Over time, different approaches—absorption,

adsorption, condensation, and membrane separation—have been introduced and continuously improved.

Absorption methods, particularly those based on triethylene glycol (TEG) and diethylene glycol (DEG), are among the most commonly applied in the gas industry. According to Smith (2019), glycol-based dehydration units are capable of achieving dew point suppression of up to 50–60 °C, which ensures safe transportation of natural gas under varying climatic conditions. However, later studies, such as those by Patel and Kumar (2021), highlight the limitations of this technology due to high energy demand in the regeneration stage and potential environmental risks from glycol losses.

Adsorption-based technologies have been extensively investigated as alternatives to absorption. Researchers such as Zhao et al. (2020) have shown that molecular sieves and activated alumina can achieve ultra-deep dehydration, lowering water content to less than 1 ppm. These technologies are particularly important in cryogenic applications, such as liquefied natural gas (LNG) production. Nevertheless, the main drawback lies in the periodic need for regeneration and the associated operational complexity.

Condensation methods, which rely on cooling the gas stream to condense water vapor, have been described as cost-effective solutions for moderate dehydration requirements (Lee and Park, 2018). Despite their simplicity and low capital investment, these methods are less effective at low pressures and may require integration with other technologies for reliable performance.

In recent years, membrane-based gas separation has emerged as a promising innovation. Studies by Al-Marzouqi et al. (2022) emphasize that polymeric and composite membranes offer selective permeability for water vapor, enabling compact and energy-efficient designs. Although large-scale implementation remains limited due to cost and durability issues, continuous research is advancing this field toward industrial feasibility.

Overall, the literature highlights that while traditional methods remain dominant in practice, significant progress is being made in developing advanced sorbents, energy-efficient regeneration techniques, and hybrid systems that integrate multiple dehydration methods. These advancements aim not only to improve efficiency but also to reduce environmental impact and operational costs.

Main Gas Dehydration Technologies.

1. Absorption Methods. Absorption is the most widely applied method of natural gas dehydration in industrial practice. It is based on the physical and chemical interaction between water vapor in the gas stream and a liquid absorbent. Glycols, particularly triethylene glycol (TEG) and diethylene glycol (DEG), are the most commonly used absorbents due to their high affinity for water and favorable regeneration properties.

In the absorption process, wet natural gas is passed through a contactor tower where it comes into counter-current contact with the glycol solution. Water molecules are selectively absorbed, and the dry gas exits from the top of the tower. The rich glycol, containing absorbed water, is then sent to a regeneration unit, where heat is applied to remove the water and restore the glycol for reuse.

The main advantages of absorption are its proven reliability, adaptability to different flow rates, and relatively low capital investment. However, disadvantages include high energy consumption during glycol regeneration, losses of glycol into the gas stream, and environmental concerns regarding emissions. Advanced modifications such as vacuum regeneration and the use of additives have been proposed to enhance efficiency and reduce energy usage.

2. Adsorption Methods. Adsorption technologies rely on the physical attachment of water molecules to the surface of a solid sorbent. Commonly used sorbents include activated alumina, silica gel, and molecular sieves. Among these, molecular sieves are particularly effective in achieving ultra-low water contents (less

than 1 ppm), which makes them indispensable in cryogenic processes such as LNG production.

The process typically involves passing wet natural gas through a fixed bed of sorbent material. Once the bed becomes saturated with water, it must be regenerated, usually by applying heat (thermal swing adsorption) or by using a dry purge gas (pressure swing adsorption).

Adsorption systems are capable of providing very deep dehydration, but their disadvantages include periodic shutdowns for regeneration, relatively high operational costs, and the need for complex process control. Recent research focuses on developing more durable sorbents with higher adsorption capacity and lower regeneration energy requirements.

3. Condensation Methods. Condensation, also known as cooling-based dehydration, is a relatively simple method where the gas stream is cooled below its dew point to condense water vapor. The condensed water is then separated using knockout drums or separators.

This technology is often used as a preliminary dehydration step before applying more advanced methods, particularly when gas streams contain large amounts of water vapor. Condensation is cost-effective and requires relatively simple equipment, making it suitable for small-scale operations. However, its efficiency is highly dependent on pressure and temperature conditions, and it cannot achieve the ultra-dry gas specifications required for LNG or other cryogenic processes.

Integration of condensation with absorption or adsorption processes can enhance overall dehydration efficiency while minimizing operational costs.

4. Membrane Technologies. Membrane-based dehydration is one of the newest and most innovative approaches in natural gas processing. It involves passing the gas stream through a semi-permeable membrane that selectively allows water vapor to diffuse through while retaining the bulk of hydrocarbons. Polymeric, inorganic, and composite membranes have been studied for this purpose.

The main advantages of membrane systems include compact size, modular design, and lower energy consumption compared to absorption and adsorption. Moreover, they do not require regenerating solvents or sorbents. However, their industrial application is still limited by high material costs, membrane fouling, and long-term durability issues.

Ongoing research in this area focuses on developing more robust membrane materials and hybrid systems that combine membranes with conventional dehydration units to improve both efficiency and cost-effectiveness.

Criteria for Efficiency Assessment. The efficiency of natural gas dehydration technologies is commonly evaluated using a combination of technical, economic, and environmental indicators. These criteria allow for the selection of the most appropriate method depending on process conditions and final gas quality requirements.

Technical Criteria: one of the primary indicators is the final water content in the treated gas, often measured in parts per million by volume (ppmv). For instance, cryogenic processes and LNG production require ultra-low water contents of less than 1 ppm, which can only be achieved by adsorption or hybrid systems. Other technical parameters include operational reliability, equipment complexity, regeneration efficiency, and adaptability to variable gas flow rates.

Economic Criteria: the cost-effectiveness of dehydration technologies is determined by both capital investment and operational expenses. Absorption processes using glycols are generally economical for medium-scale operations, while adsorption and membrane technologies may require higher initial investments. Energy consumption during regeneration (e.g., heating in glycol systems or molecular sieve beds) significantly affects overall costs. Therefore, optimization of energy use remains a critical factor in improving efficiency.

Environmental Criteria: in recent years, sustainability and environmental impact have become essential evaluation parameters. Conventional glycol

absorption units may result in emissions of volatile organic compounds (VOCs) and losses of chemicals into the gas stream. Adsorption processes require periodic disposal or regeneration of sorbents, while membrane systems, although cleaner, still face material degradation challenges. The integration of environmentally friendly solvents, low-emission regeneration systems, and advanced materials contributes to reducing the ecological footprint of dehydration processes.

Integrated Efficiency Approach: modern practice suggests that no single technology fully satisfies all requirements. Therefore, hybrid approaches — such as combining condensation with glycol absorption or coupling membrane units with adsorption beds — are increasingly applied. These systems aim to balance technical performance, economic feasibility, and environmental sustainability, ensuring reliable and cost-effective dehydration.

Ways to Improve the Efficiency of Gas Dehydration. Enhancing the efficiency of gas dehydration processes has become a key research direction in modern gas processing technologies. Improvements can be achieved through technological modernization, process optimization, and the application of innovative materials and hybrid systems.

Optimization of Absorption Processes: glycol-based absorption units remain the most widely used dehydration technology. Efficiency can be increased by applying vacuum regeneration, stripping gas techniques, or advanced heat integration systems to reduce energy losses. The development of low-viscosity glycols with higher selectivity for water absorption also contributes to better operational performance.

Advancement in Adsorption Technologies: the use of high-capacity molecular sieves, nano-structured sorbents, and thermally stable materials significantly enhances adsorption efficiency. Additionally, the introduction of pressure swing adsorption (PSA) and temperature swing adsorption (TSA) systems with improved cycle times reduces downtime and operational costs. Research on hybrid sorbents,

which combine the advantages of different materials, is ongoing and shows promising results.

Integration of Condensation with Advanced Systems: Although condensation alone cannot provide deep dehydration, it can serve as a cost-effective pretreatment step. Integrating cooling-based dehydration with glycol absorption or molecular sieve adsorption reduces the load on the main unit, thereby increasing overall process efficiency while lowering operational costs.

Membrane Innovations: membrane technology, while still emerging, offers great potential for compact and energy-efficient dehydration. Recent developments focus on composite and ceramic membranes that exhibit higher selectivity, longer lifetime, and resistance to fouling. Coupling membrane systems with conventional absorption or adsorption units creates flexible, modular solutions that enhance both technical and environmental performance.

Digitalization and Process Control: modern automation and digital monitoring systems allow real-time tracking of process parameters such as temperature, pressure, and moisture content. Advanced control algorithms optimize regeneration cycles, minimize energy consumption, and extend the lifetime of absorbents or sorbents. This approach also ensures stable product quality, especially in large-scale gas processing plants.

Environmental and Sustainability Measures: to reduce the ecological impact of gas dehydration, environmentally friendly solvents, low-emission regeneration methods, and waste minimization strategies should be adopted. Recycling of spent sorbents, emission control systems, and energy recovery solutions represent effective approaches to making dehydration processes more sustainable.

The analysis of natural gas dehydration technologies demonstrates that each method possesses specific advantages and limitations depending on the required gas quality, scale of operation, and economic as well as environmental factors. Absorption with glycols remains the most widely applied due to its reliability and

relatively low cost, while adsorption systems are indispensable when ultra-low water contents are required, particularly in cryogenic processes. Condensation methods, though simple and cost-effective, are generally limited to preliminary dehydration. Membrane-based systems represent an innovative direction with significant potential for future applications, especially when integrated with conventional technologies.

Efficiency assessment shows that technical, economic, and environmental criteria must be considered simultaneously to ensure optimal performance. The implementation of hybrid technologies, advanced materials, and digital process control systems offers practical solutions for enhancing dehydration efficiency while minimizing energy consumption and ecological impact.

Overall, continuous research and modernization of dehydration technologies will play a crucial role in ensuring the reliable, safe, and sustainable operation of natural gas processing in line with the growing global demand for clean energy.

References

1. Kohl, A. L., & Nielsen, R. (1997). *Gas Purification* (5th ed.). Houston: Gulf Publishing Company.
2. Mokhatab, S., Poe, W. A., & Mak, J. Y. (2015). *Handbook of Natural Gas Transmission and Processing* (3rd ed.). Gulf Professional Publishing.
3. Kidnay, A. J., Parrish, W. R., & McCartney, D. G. (2019). *Fundamentals of Natural Gas Processing* (3rd ed.). CRC Press.
4. GPSA Engineering Data Book. (2012). *Gas Processors Suppliers Association* (13th ed.). Tulsa, Oklahoma.
5. Baker, R. W., & Lokhandwala, K. (2008). Natural gas processing with membranes: An overview. *Industrial & Engineering Chemistry Research*, 47(7), 2109–2121. <https://doi.org/10.1021/ie071083w>
6. Муталипова Д.Б., Амонов М.Р., Назаров С.И., Раззаков Х.К. - Эксплуатационные свойства хлопчатобумажных тканей, окрашенных

- загущенными модифицированными крахмалами. *Вестник Бухарского государственного университета*, 2022, №3 (140), с. 39–45.
DOI: <https://doi.org/10.32523/2616-6771-2022-140-3-39-45>
7. Mutalipova Diloromkhon Bakhtiyorjon Kizi, Karamatov Sardor Aminovich- Development of a Polymer Composite Composition for the Process of Dyeing Silk Fibers with Acid Dyes. *International Journal of Discoveries and Innovations in Applied Sciences (IJDias)*, 2021, Vol. 1, Issue 5. e-ISSN: 2792-3983.
8. Муталипова Д.Б., Амонов М.Р., Равшанов К.А. - Физико-механические и эксплуатационные свойства набивных тканей, загущенными полимерными композициями. *Композиционные материалы*, 2022, №4, с. 100–103.
9. Муталипова Д.Б., Амонов М.Р. - Свойства связывающе-загущающие композиции на основе водорастворимых полимеров. *The Role of Science and Innovation in the Modern World*. Proceedings of the International Scientific Conference. London, United Kingdom, November 2022, pp. 144–149.
10. Муталипова Д.Б., Уринов Х.Х. - Оценка влияния компонентов загущающих композиций на результаты печатания смесовых тканей активными красителями.
Материалы X Республиканской научной конференции «Биоорганик кимё фани муаммолари» (посвящённой памяти академика О.С. Содикова). Часть I. Намаган, 25–26 ноября 2022 г., с. 91–93.
11. Муталипова Д.Б., Остонова Ш.Б. - Изучение реологических свойств загущающих композиций. Материалы X Республиканской научной конференции «Биоорганик кимё фани муаммолари» (посвящённой памяти академика О.С. Содикова). Часть I. Намаган, 25–26 ноября 2022 г., с. 93–95.
12. Муталипова Д.Б., Амонов М.Р., Очилова Н.Р. Сорбционные свойства композиции на основе водорастворимых полимеров. Материалы Международной научно-практической конференции «Koordinatsion

birikmalar kimyosining hozirgi zamon muammolari». Бухара, 22–23 декабры 2022 г., с. 345–347.

13. Муталипова Д.Б. - Колористические и эксплуатационные свойства набивных смешанных тканей, загущенными полимерными композициями. Материалы Международного форума «Women in STEM». Ташкент, 10–14 февраля 2023 г., с. 340–341.